

# Granit 1911i

## Wireless Industrial-Grade Area-Imaging

The Granit™ 1911i wireless industrial-grade area-imaging scanner is designed to withstand the varied demands that exist in harsh working environments. Featuring a custom built housing that is redefining the standard for scanner reliability, the IP65 rated Granit 1911i is built to survive 5,000 3.3' (1 m) tumbles and 50 drops to concrete from 6.5' (2 m) even at -4°F (-20°C). As a result, businesses can expect to experience minimal device downtime and a lower overall cost of ownership.

Powered by Honeywell's Adaptus™ 6.0 imaging technology and its revolutionary decoding architecture, the Granit 1911i provides users with the same exceptional bar code reading performance as the best-in-class Xenon™ series of area-imaging scanners. From poorly printed and damaged codes to low density linear codes, the Granit 1911i is built to read virtually all bar codes with ease—supporting maximum operator productivity with its enhanced illumination, crisp laser aiming and extended depth-of-field.

The Granit 1911i also incorporates a Bluetooth® Class 1, v2.1 radio, enabling wireless connectivity and unrestricted movement up to 300 feet (100 m) from the base. Additionally, with Honeywell's Shift-PLUS power management system users can expect up to 14 hours of battery life reducing the cost associated with battery backups and replacements. A paging system is also available for added convenience to assist with locating misplaced scanners.

Created specifically for applications in which high performance scanning is expected and durability is highly valued, the Granit 1911i is the optimal solution for businesses operating in unpredictable conditions.



## Features

- **Class-Leading Durability:** The custom-built IP65-rated housing is able to withstand 5,000 3.3' (1 m) tumbles and survive 50 drops from 6.5' (2 m) at -4°F (-20°C) reducing service costs and increasing device uptime
- **Wireless Connectivity:** Bluetooth® Class 1, v2.1 radio enables movement up to 300' (100 m) from base, and reduces interference with other wireless systems. Up to 7 imagers can communicate with a single base, reducing the total cost of ownership
- **TotalFreedom™ 2.0:** The second-generation of Honeywell's area-imaging development platform enables the loading and linking of multiple applications to enhance image decoding, data formatting and image processing—eliminating the need for host system modifications
- **Long-Lasting Lithium-Ion Battery:** Powers up to 50,000 scans per full charge and is removable without tools ensuring maximum uptime for operations running multiple shifts
- **Extended Linear Depth of Field:** Scans out-of-reach items with ease and allows users to scan 20 mil linear codes out to 29.5" (75 cm) without sacrificing performance on 2D codes
- **Remote MasterMind™ Scanning Management Software:** Quick and convenient solution for IT administrators seeking to manage the scanners within their network from a single remote location

# Granit 1911i Technical Specifications

## Wireless

Radio/Range	2.4 to 2.5 GHz (ISM Band) Adaptive Frequency Hopping Bluetooth v2.1: Class 1: 100m (300') line of sight
Data Rate (Transmission Rate)	Up to 1 Mbps/S
Battery	2000 mAh Li-ion minimum
Number of Scans	Up to 50,000 scans per charge
Expected Hours of Operation	14 hours
Expected Charge Time*	4.5 hours

## Mechanical/Electrical

	Scanner (1911IER-3)	Charger/Communication Base (COB02/CCB02-100BT-07N)
Dimensions (LxWxH)	133 mm x 75 mm x 195 mm (5.2" x 2.9" x 7.6")	250 mm x 103 mm x 65 mm (9.9" x 4.1" x 2.6")
Weight	380 g (13.4 oz)	290 g (10.2 oz)
Operating Power (Charging)	N/A	5 W (1A @ 5 V)
Non-Charging Power	N/A	0.6 W (0.12A @ 5 V)
Host System Interfaces	N/A	USB, Keyboard Wedge, RS232 TTL

## Environmental

	Scanner (1911IER-3)	Charger/Communication Base (COB02/CCB02-100BT-07N)
Operating Temperature**	-20°C to 50°C (-4°F to 122°F)	-20°C to 50°C (-4°F to 122°F)*
Storage Temperature	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)
Humidity	Up to 95% relative humidity, non-condensing	Up to 95% relative humidity, non-condensing
Drop	Designed to withstand 50 2 m (6.5') drops to concrete at -20°C	Designed to withstand 50 1.2 m (4') drops to concrete at -20°C
Tumble	5,000 1m (40') tumbles	5,000 1m (40') tumbles
Environmental Sealing	IP65	IP51
Light Levels	0 to 100,000 lux (9,290 foot-candles)	N/A
ESD	±20Kv air discharge, ±8kV contact discharge	±20Kv air discharge, ±8kV contact discharge

## Scan Performance

Scan Pattern	Area Imager (838 x 640 pixel array)
Motion Tolerance	Up to 610 cm/s (240 in/s) at 16.5 cm (6.5") and 381 cm/s (150 in/s) at 25 cm (10.0") for 13 mil UPC
Scan Angle	ER Focus: Horizontal: 31.6°; Vertical: 24.4°
Symbol Contrast	20% minimum reflectance difference
Pitch, Skew	45°, 65°
Warranty	3 year factory warranty (Note: battery warranty is 1 year)

\*battery charging only occurs between 5° C and 40°C; \*\*with industrial grade cable ordered separately

For a complete listing of all compliance approvals and certifications, please visit [www.honeywellaidc.com/compliance](http://www.honeywellaidc.com/compliance)

For a complete listing of all supported bar code symbologies, please visit [www.honeywellaidc.com/symbologies](http://www.honeywellaidc.com/symbologies)



### For more information:

[www.honeywellaidc.com](http://www.honeywellaidc.com)

### Honeywell Scanning & Mobility

9680 Old Bailes Road  
Fort Mill, SC 29707  
800.582.4263  
[www.honeywell.com](http://www.honeywell.com)

Typical Performance*	Extended Range (ER)
Narrow Width	
7.5 mil Code 39	48 mm - 310 mm (1.9" - 12.2")
13 mil UPC	15 mm - 543 mm (0.6" - 21.4")
20 mil Code 39	15 mm - 749 mm (0.6" - 29.5")
6.7 mil PDF417	69 mm - 226 mm (2.7" - 8.9")
10 mil DM**	71 mm - 261 mm (2.8" - 10.3")
20 mil QR	20 mm - 495 mm (0.8" - 19.5")
Resolution 1D Code 39	5 mil (0.127 mm)
Resolution 2D DM**	7.5 mil (0.191 mm)
*Performance may be impacted by bar code quality and environmental conditions	
**Data Matrix (DM)	

# Honeywell



800 729 0236  
www.logiscenter.us



0241 9550 9225  
www.logiscenter.de



01 82 88 44 70  
www.logiscenter.fr



020 3318 8265  
www.logiscenter.co.uk



0720 115814  
www.logiscenter.at



02 58 80 583  
www.logiscenter.be



911 433 048  
www.logiscenter.com



02 4792 1697  
www.logiscenter.it



308 800 842  
www.logiscenter.pt

## About LOGISCENTER

Logiscenter is the leading provider of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

## Reasons to work with us

**Our customers come first.** Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

**The best brands.** We offer products from the best manufacturers worldwide.

**Expert technical support team.** Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

**Largest stock.** We have a permanent stock of more than 60,000 products.

**Same-day shipping.** For all orders placed and confirmed before 16:00 on working days.

**Best prices.** With Logiscenter, you can be sure that you are paying a fair price for your products, we will not overcharge you.

**Easy returns.** Damaged or defective products can be returned easily, for an exchange or reimbursement.



## All Brands Technical Service


## Our Brands




## Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables  
(labels, ribbons, PVC cards)